

GRAIN MILLERS Triticale

Official Purchasing Specification

Quality Standards

	Spec	Min/Max
Test Weight	56	50
Moisture	13%	13.5%
Plump	70%	60%
Thins	0%	5%

Foreign Material

	Spec	Min/Max
FM	0%	3%
Total Other	0%	2%
Grains		
Ergot	0%	.04%

Damage

	Spec	Min/Max
Total Damage	0%	4%
Vomitoxin	0 ррт	1 ppm
Heated	0%	0.2%
Falling #	170	150

Test Weight Conversions

Lb/W.bu	g/0.5 L	Lb/W.bu	g/0.5 L
49	316	54	348
49.5	319	54.5	351
50	322	55	354
50.4	325	55.5	357
50.9	328	56	361
51.5	332	56.5	364
52	335	57	367
52.5	338	<i>57.5</i>	370
52.9	341	58	374
53.5	345	58.5	377

Discounts may apply to any grain delivered out of spec.

- » FM –Thru 8/64" triangle sieve
- » Plump On top of 6/64" slotted sieve
- » Moisture Tested on Dickey John

Pest/Pesticide/Odor Restrictions

- Triticale must NOT contain signs of infestation (dead or alive) or insect damaged kernels
- Triticale which has been treated with glyphosate as a pre-harvest desiccant will not be accepted
- Triticale must not contain detectable levels of pesticide, chemicals, or any objectionable odors

Contacts

Conventional:
Beth Stebbins
952-983-1279

beth.stebbins@grainmillers.com

Dan Patton 952-983-1278 dan.patton@grainmillers.com Conventional Triticale Discount Schedule (Based on W.Bu, US\$)

Foreign Material (FM)

• All FM is deducted as dockage